



EasyGate Elite-G

EasyGate Elite-G / Elite-R

Type

Swing technology
 1 wing / 2 wings
 G model - round front
 R model - square front

Safety & Security Detection

- 18 pairs of IR sensors / 26 pairs of IR sensors*
- Safety & Security levels
- Tailgating / Cross over detection

Dimensions

Cabinet height	990 mm	38.98"
Cabinet length Elite	1 240 mm	48.80"
Cabinet width	132 mm	5.20"
Barrier height standard	990 mm	38.98"
Barrier height max.	1 800 mm	70.87"
Passage width standard ^[1]	650 mm	25.59"
Passage width max. ^[1]	1 100 mm	43.31"

for height of glass wing up to 1 400 mm

max 920 mm 36.22"

for height of glass wing up to 1 800 mm

Special feature*

Wide passage lane
 Arc layout
 Flag wing



EasyGate Elite-G / 990 mm



EasyGate Elite-R / 1 800 mm

* Optional [1] For 2 wings type



EasyGate Elite-R

Materials and Colours

Frame	black RAL
Covers	black RAL
Top Lid	black glass
Barriers	tempered glass barrier panels (10 mm / 0.39")

Operating Environment

Indoor

Drive Mechanism

Fail-Safe
MCBF 5 000 000

Stand-by Power Consumption

22.6 W

Emergency Mode

Open automatically in the exit direction

Optional Accessories

- RFID reader bracket (flush mounted)
- Access Light / Edge Light / Lane Light / Wing Light
- WAV player
- Hinge capping
- Pressure sensing top
- RF remote control
- EasyTouch / TouchPanel / T-MON SW
- SuperCap (emergency power back-up)
- Alternative surface finishes / Optional top finishes
- Integration of LiftCall / Card collector / BarCode scanner
- Ramp LT

